


**1421A Paired - Low Capacitance Computer Cables for EIA RS-232/422**

	<p>For more information please call <b>1-800-Belden1</b></p> <p><u>See Put-ups and Colors</u></p> <p><b>Color Code Chart : No. 5 for Paired Cables (Western Electric Standard).pdf</b></p>
---	--

**Description:**

24 AWG stranded (7x32) tinned copper conductors, twisted pairs, Datalene® insulation, overall 100% Beldfoil® shield, 24 AWG stranded tinned copper drain wire, PVC jacket.

**PHYSICAL CHARACTERISTICS:**

**CONDUCTOR:**

Number of Pairs	4
Total Number of Conductors	8
AWG	24
Stranding	7x32
Conductor Material	TC - Tinned Copper

**INSULATION:**

Insulation Material Trade Name	Datalene®
Insulation Material	FPE - Foam Polyethylene

**Pair Color Code Chart :**

Number	Color	Number	Color
1	White/Blue & Blue/White	3	White/Green & Green/White
2	White/Orange & Orange/White	4	White/Brown & Brown/White

**OUTER SHIELD:**

Outer Shield Material Trade Name	Beldfoil®
Outer Shield Type	Tape
Outer Shield Material	Aluminum Foil-Polyester Tape
Outer Shield % Coverage	100 %

**OUTER SHIELD DRAIN WIRE :**

Outer Shield Drain Wire AWG	24
Outer Shield Drain Wire Stranding	7x32
Outer Shield Drain Wire Conductor Material	TC - Tinned Copper

**OUTER JACKET:**

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

## 1421A Paired - Low Capacitance Computer Cables for EIA RS-232/422

### OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.280 in.
--------------------------	----------

### MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +80°C
Non-UL Temperature Rating	80°C (UL AWM Style 2919)
Bulk Cable Weight	32.6 lbs/1000 ft.
Max. Recommended Pulling Tension	44 lbs.
Min. Bend Radius (Install)	2.75 in.

### APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

#### APPLICABLE STANDARDS:

NEC/(UL) Specification	CM
CEC/C(UL) Specification	CM
AWM Specification	UL Style 2919 (30 V 80°C)

#### FLAME TEST:

UL Flame Test	UL1581 Vertical Tray
---------------	----------------------

#### PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

### ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	100 Ohms
Nom. Inductance	.213 µH/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	13 pF/ft
Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	22 pF/ft
Nominal Velocity of Propagation	78 %
Nom. Conductor DC Resistance @ 20 Deg. C	24 Ohms/1000 ft
Maximum Outer Shield DC Resistance @ 20 Deg. C	14.4 Ohms/1000 ft
Max. Operating Voltage - UL	30 V RMS (UL AWM Style 2919); 300 V RMS
Max. Recommended Current	1.8 Amps per conductor @ 25°C

#### NOTES:

Notes	Datalene® insulation features include low dielectric constant and a dissipation factor for high-speed, low distortion data handling. Physical properties include good crush resistance and light weight.
-------	--

### PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
1421A 0601000	4 PR #24 FHDPE FS PVC	1000	37	CHROME	C
1421A 060500	4 PR #24 FHDPE FS PVC	500	18.5	CHROME	

---

**1421A Paired - Low Capacitance Computer Cables for EIA RS-232/422**

C = CRATE REEL PUT-UP.

Revision Number: 1      Revision Date: 01-30-2004

---

© 2004 Belden Wire & Cable Company  
All Rights Reserved.

Although Belden Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.